



Hospital

# Flight 60<sup>®</sup>

## Acute Care Ventilation

Remarkable performance and features in a portable and intuitive package. The Flight 60 ventilator is designed to address a wide range of hospital needs while improving patients' comfort & independence.

### Full Ventilation Package

- Advanced ventilation modes
  - Pressure and Volume
  - Invasive & non-invasive
- Pediatric to adult - 30 ml - 2.2 liter
- Complete graphic display
  - Waveforms and loops
  - Trends - display up to 72 hours
- Exhaled volume monitoring

### Safe, Intuitive and Mobile

- Extensive alarm system
- Oxygen sensor - built in
- Simple to use with 7" color touch screen
- Lightweight & portable
- High pressure and low flow O<sub>2</sub> ports
- Fully independent internal compressor
- Easily connecting to hospitals' IT systems



# FLIGHT 60

## Your Partner in Ventilation

### Technical Specifications

MODES	
	ACMV
	SIMV
	SPONT (CPAP, BPAP)
CONTROLS	
Breath Types	Pressure Control Pressure Support Volume Control
NPPV	ON/OFF (leak compensation up to 30 LPM)
SIGH	ON/OFF
Tidal Volume	30 to 2,200 ml
Breath Rate	1 to 99 b/min
Inspiration Time (Ti)	0.1 to 3.0 sec
Flow	2 to 100 L/min
Pressure Control	5 to 60 cmH <sub>2</sub> O
Pressure Support (PSV)	0 to 60 cmH <sub>2</sub> O
PEEP/CPAP	0 to 30 cmH <sub>2</sub> O
Pressure Trigger	-9.9 to -0.1 cmH <sub>2</sub> O
Flow Trigger	1 to 20 LPM
Rise Profile	5 levels
PSV Ti	0.1 to 3 sec
PSV Flow Termination	10% to 70%
Volume Control	Time/Flow
Flow Waveform	Square/Descending
FiO <sub>2</sub>	21% to 100%
FiO <sub>2</sub> Sensor	ON, OFF, Calibrate
Manual Breath	0 to 3 sec
Panel Lock	ON/OFF
Trends	ON/OFF/Clear
ALARMS (variable)	
Alarm Prioritization	3 Levels – Caution, Medium, High
Low Minute Volume	0.0 to 50 L/min
Low Pressure	OFF, 1 to 98 cmH <sub>2</sub> O
High Pressure	4 to 99 cmH <sub>2</sub> O
High Minute Volume	0.1 to 50 L/min
High FiO <sub>2</sub>	31% to 99%, OFF
Low FiO <sub>2</sub>	OFF, 22% to 90%
High Rate	OFF, 1 to 99 bpm
Low Rate	OFF, 1 to 99 bpm
Low Vte	OFF, 10 to 2,200ml
Low Vti	OFF, 10 to 2,200ml
Apnea/Back-Up Ventilation	10-60 sec
ALARMS (automatic)	
	Check Circuit (Circuit Disconnect), Low/Empty Battery
OXYGEN	
High Pressure	35 to 90 psi O <sub>2</sub> (0-100%)
Low Flow Port	0 to 15 L/min O <sub>2</sub> (0-70%)
Low Flow Blending Bag	0 to 15 L/min O <sub>2</sub> (0-100%)

MONITORED PARAMETERS	
Waveforms	Pressure, Flow, Volume
Loops	Pressure/Volume & Flow/Volume
Trends	Rate, Peak Inspiratory Pressure & Vte (up to 72 hours)
Airway Pressure LED Gauge	-10 to 120 cmH <sub>2</sub> O
Peak Inspiratory Pressure	0 to 120 cmH <sub>2</sub> O
Base Pressure	0 to 99 cmH <sub>2</sub> O
Mean Pressure	0 to 99 cmH <sub>2</sub> O
Exhaled Tidal Volume	0 to 10L
Exhaled Minute Volume	0 to 99L
Inhaled Tidal Volume	0 to 10L
Inhaled Minute Volume	0 to 99L
Actual Breath Rate	0 to 99 b/min
Peak Inspiratory Flow	1 to 120 L/min
FiO <sub>2</sub>	21% to 100%
I:E Ratio	1:99 to 3:1
Battery Level	100% to 0%, Low, Empty
TECHNICAL SETTINGS	
Buzzer Level	LOW/HIGH
Keypad Buttons	Keypad buttons with audible indicator
Power Save	ON/OFF
Languages	English, French, German, Greek, Hungarian, Italian, Polish, Portuguese, Russian, Spanish, Turkish
SIZE AND WEIGHT	
Dimensions (WxLxH)	29 x 28 x 25 cm / 11.4" x 11.0" x 9.8"
Weight	6.3 Kg / 13.9 lbs
POWER SUPPLY	
AC Power Inlet	100 to 240 VAC, 50-60Hz
DC Power Inlet	12 to 15 VDC
Internal Batteries	Hot Swappable 12 hours operation
Charging Time	Up to 3 hours
COMMUNICATIONS	
USB x2	Download Logs, SW Upgrade
LAN RJ45	Networking
RS232 x2	Remote Alarm and Monitoring
RS485	Communication
ENVIRONMENTAL	
Operation Temperature	-18°C to 50°C / -0.4°F to 122°F
Storage Temperature	-20°C to 71°C / -4.0°F to 160°F
Relative Humidity	15% to 95% at 31°C / 88°F
Operation Altitude	110 kPa to 70 kPa
Water/Dust Resistance	IP34 (splash proof)
STANDARDS	
	IEC 60601-1 ,IEC 60601-1-2 ,IEC 60601-2-12, ASTM 1246F , ISO 10651-2/3, RTCA DO-160 F

LIT-0025 Rev A01