



Emergency

Flight 60[®]

Respond With Confidence!

A complete independent ventilation solution for your emergency transports in a portable and intuitive package. From CPAP patients to fully ventilator-dependent patients, Flight 60 provides you with advanced capabilities when, where and for as long as you need them.

Easy, Intuitive & Mobile

- Simple to use with 7" color touch screen
- Lightweight & portable
- High pressure and low-flow O₂ ports
- Airborne Certified DO-160F
- 12 hours internal battery
- Easy to read in full daylight

Complete Ventilation Suite

- All pressure and volume modes
- Invasive and non-invasive.
- Pediatric to adult ventilation - 30 ml - 2.2 liter
- Oxygen sensor – built in

Accessories



F60 Rail Mount



F60 in-use carry case



FLIGHT 60

Your Partner in Ventilation

Technical Specifications

MODES	
	ACMV
	SIMV
	SPONT (CPAP, BPAP)
	Volume Guarantee (PRVC)
	B-Lev (Bi-Phasic, APRV)

CONTROLS	
Breath Types	Pressure Control Pressure Support Volume Control
NPPV	ON/OFF (leak compensation up to 30 LPM)
VG Mode	VtG (Tidal Volume Guarantee) MVG (Minute Volume Guarantee)
SIGH	ON/OFF
Synchronized Nebulizer	ON/OFF
Nebulization Period	OFF, 5 to 60 min
2min 100% O ₂ Function	ON/OFF
Tidal Volume	30 to 2,200 ml
Breath Rate	1 to 99 b/min
Inspiration Time (Ti)	0.1 to 3.0 sec
Flow	2 to 100 L/min
Pressure Control	5 to 60 cmH ₂ O
Pressure Support (PSV)	0 to 60 cmH ₂ O
PEEP/CPAP	0 to 30 cmH ₂ O
Pressure Trigger	-9.9 to -0.1 cmH ₂ O
Flow Trigger	1 to 20 LPM
Rise Profile	5 levels
PSV Ti	0.1 to 3 sec
PSV Flow Termination	10% to 70%
Volume Control	Time/Flow
Flow Waveform	Square/Descending
FiO ₂	21% to 100%
FiO ₂ Sensor	ON, OFF, Calibrate
Manual Breath	0 to 3 sec
Panel Lock	ON/OFF
Trends	ON/OFF/Clear

VG Mode Controls	
Target VtG	30 to 2,200 ml
PSV min	0 to 60 cmH ₂ O
PSV max	5 to 60 cmH ₂ O

B-Lev Controls	
P High	3 to 60 cmH ₂ O
P Low	0 to 30 cmH ₂ O
T High (Ti)	1 to 15 sec
T Low	0.5 to 5 sec
Inverse I:E	30:1

ALARMS (variable)	
Alarm Prioritization	3 Levels – Caution, Medium, High
Low Minute Volume	0.0 to 50 L/min
Low Pressure	OFF, 1 to 98 cmH ₂ O
High Pressure	4 to 99 cmH ₂ O
High Minute Volume	0.1 to 50 L/min
High FiO ₂	31% to 99%, OFF
Low FiO ₂	OFF, 22% to 90%
High Rate	OFF, 1 to 99 bpm
Low Rate	OFF, 1 to 99 bpm
Low Vte	OFF, 10 to 2,200ml
Low Vti	OFF, 10 to 2,200ml
Apnea/Back-Up Ventilation	10-60 sec

ALARMS (automatic)	
	Check Circuit (Circuit Disconnect), Low/Empty Battery, O ₂ Supply Failed, Check O ₂ Sensor

MONITORED PARAMETERS	
Waveforms	Pressure, Flow, Volume
Loops	Pressure/Volume & Flow/Volume
Trends	Rate, Peak Inspiratory Pressure & Vte (up to 72 hours)
Airway Pressure LED Gauge	-10 to 120 cmH ₂ O
Peak Inspiratory Pressure	0 to 120 cmH ₂ O
Base Pressure	0 to 99 cmH ₂ O
Mean Pressure	0 to 99 cmH ₂ O
Exhaled Tidal Volume	0 to 10L
Exhaled Minute Volume	0 to 99L
Inhaled Tidal Volume	0 to 10L
Inhaled Minute Volume	0 to 99L
Actual Breath Rate	0 to 99 b/min
Peak Inspiratory Flow	1 to 120 L/min
FiO ₂	21% to 100%
I:E Ratio	1:99 to 3:1
Battery Level	100% to 0%, Low, Empty

TECHNICAL SETTINGS	
Buzzer Level	LOW/HIGH
Keypad Buttons	Keypad buttons with audible indicator
Power Save	ON/OFF
Languages	English, French, German, Greek, Hungarian, Italian, Polish, Portuguese, Russian, Spanish, Turkish

SIZE AND WEIGHT	
Dimensions (WxLxH)	29 x 28 x 25 cm / 11.4" x 11.0" x 9.8"
Weight	6.3 Kg / 13.9 lbs 6.9 Kg / 15.2 lbs (with integrated mixer)

OXYGEN	
O ₂ Mixer (optional)	Internal integral, electronically controlled
High Pressure	35 to 90 psi O ₂ (0-100%)
Low Flow Port	0 to 15 L/min O ₂ (0-70%)
Low Flow Blending Bag	0 to 15 L/min O ₂ (0-100%)

POWER SUPPLY	
AC Power Inlet	100 to 240 VAC, 50-60Hz
DC Power Inlet	12 to 15 VDC
Internal Batteries	Hot Swappable 12 hours operation
Charging Time	Up to 3 hours

COMMUNICATIONS	
USB x2	Download Logs, SW Upgrade
LAN RJ45	Networking
RS232 x2	Remote Alarm and Monitoring
RS485	Communication

ENVIRONMENTAL	
Operation Temperature	-18°C to 50°C / -0.4°F to 122°F
Storage Temperature	-20°C to 71°C / -4.0°F to 160°F
Relative Humidity	15% to 95% at 31°C / 88°F
Operation Altitude	110 kPa to 70 kPa
Water/Dust Resistance	IP34 (splash proof)

STANDARDS	
	IEC 60601-1 ,IEC 60601-1-2 ,IEC 60601-2-12, ASTM 1246F , ISO 10651-2/3, RTCA DO-160 F